

TEMPERATURE CONVERSION TABLE

C	F	C	F	C	F	C	F	C	F
-80	-112.0	1	33.8	31	87.8	61	141.8	91	195.8
-70	-94.0	2	35.6	32	89.6	62	143.6	92	197.6
-60	-76.0	3	37.4	33	91.4	63	145.4	93	199.4
-50	-58.0	4	39.2	34	93.2	64	147.2	94	201.2
-45	-49.1	5	41.0	35	95.0	65	149.0	95	203.0
-40	-40.0	6	42.8	36	96.8	66	150.8	96	204.8
-35	-31.0	7	44.6	37	98.6	67	152.6	97	206.6
-30	-22.0	8	46.4	38	100.4	68	154.4	98	208.4
-25	-13.0	9	48.2	39	102.2	69	156.2	99	210.2
-20	-4.0	10	50.0	40	104.0	70	158.0	100	212.0
-19	-2.2	11	51.8	41	105.8	71	159.8	105	221.0
-18	-0.4	12	53.6	42	107.6	72	161.6	110	230.0
-17	1.4	13	55.4	43	109.4	73	163.4	115	239.0
-16	3.2	14	57.2	44	111.2	74	165.2	120	248.0
-15	5.0	15	59.0	45	113.0	75	167.0	130	266.0
-14	6.8	16	60.8	46	114.8	76	168.8	140	284.0
-13	8.6	17	62.6	47	116.0	77	170.6	150	302.0
-12	10.4	18	64.4	48	118.4	78	172.4	160	320.0
-11	12.2	19	66.2	49	120.2	79	174.2	170	338.0
-10	14.0	20	68.0	50	122.0	80	176.0	180	356.0
-9	15.8	21	69.8	51	123.8	81	177.8	190	374.0
-8	17.6	22	71.6	52	125.6	82	179.6	200	392.0
-7	19.4	23	73.4	53	127.4	83	181.4	250	482.0
-6	21.2	24	75.2	54	129.2	84	183.2	300	572.0
-5	23.0	25	77.0	55	131.0	85	185.0	350	662.0
-4	24.8	26	78.8	56	132.8	86	186.8	400	752.0
-3	26.6	27	80.6	57	134.6	87	188.6	500	932.0
-2	28.4	28	82.4	58	136.4	88	190.4	600	1112.0
-1	30.2	29	84.2	59	138.2	89	192.2	700	1292.0
0	32.0	30	86.0	60	140.0	90	194.0	800	1472.0
								900	1652.0
								1000	1832.0